

Mayplas

The Insulation Converter

563 Black Polythene Enclosed Glassfibre Ceiling Pad

Product Guide

Mayplas Glassfibre Ceiling Pad is designed for the additional thermal insulation of suspended ceiling systems

Black Polythene Enclosed Glassfibre is especially suitable for "high tech" or sensitive areas where loose fibres could cause problems



- * No loose fibres in ceiling void
- * Excellent thermal insulation
- * Black Polythene Enclosed Glassfibre
- * In sizes for easy access to ceiling void



FM 11012

Peel Industrial Estate - Chamberhall St - Bury - Lancashire BL9 OLU

Tel: 0161-447-8320 Fax: 0161-447-8333 E-mail: sales@mayplas.co.uk

Mayplas

Product Specification

563 Black Polythene Enclosed Glassfibre Ceiling Pad

The product consists of glassfibre mat
totally enclosed in 250 gauge black polythene

<u>Pad Sizes:</u>	25mm x 600mm x 600mm (20 per pack) 7.20 m ²
	25mm x 600mm x 1200mm (10 per pack) 7.20 m ²
	60mm x 600mm x 600mm (20 per pack) 7.20 m ²
	60mm x 600mm x 1200mm (10 per pack) 7.20 m ²
	80mm x 600mm x 600mm (20 per pack) 7.20 m ²
	80mm x 600mm x 1200mm (10 per pack) 7.20 m ²
	100mm x 600mm x 600mm (20 per pack) 7.20 m ²
	100mm x 600mm x 1200mm (10 per pack) 7.20 m ²
	150mm x 580mm x 600mm (10 per pack) 3.48 m ²
	150mm x 600mm x 1160mm (5 per pack) 3.48 m ²
	170mm x 580mm x 600mm (10 per pack) 3.48 m ²
	170mm x 600mm x 1160mm (5 per pack) 3.48 m ²
	200mm x 580mm x 600mm (10 per pack) 3.48 m ²
	200mm x 600mm x 1160mm (5 per pack) 3.48 m ²

Black Polythene Enclosing: 250 gauge
Vapour Check to BS 2972:1989

Glassfibre Nominal Density: 10 kgs/m³: 60, 80, 100, 150, 170 & 200mm
20 kgs/m³: 25mm

Thermal Resistance (R value): 25mm: 0.75 m²K/W
50mm: 1.51 m²K/W
60mm: 1.35 m²K/W
80mm: 1.80 m²K/W
100mm: 2.25 m²K/W
150mm: 3.40 m²K/W
170mm: 3.85 m²K/W
200mm: 4.50 m²K/W

Glassfibre Fire Rating: Non combustible
to BS 476: Part 4 1970 (1984)

Fixing

Mayplas 563 Ceiling Pads are laid on to the suspended ceiling during the installation process



FM 11012

Peel Industrial Estate - Chamberhall St - Bury - Lancashire BL9 OLU

06/03

Tel: 0161-447-8320 Fax: 0161-447-8333 E-mail: sales@mayplas.co.uk